

Seeker Series, 36 Cell Modules

Electrical Data¹ All data refers to STC (AM 1.5, 1000 W/m², 25°C)

| Peak Power P _{max} (Wp) | 40 | 50 | 60 | 75 | 100 | 125 | 150 |
|---|-------|-------|-------|-------|-------|-------|-------|
| Maximum Voltage V _{mpp} (V) | 18.46 | 18.31 | 18.54 | 17.91 | 17.85 | 18.0 | 18.23 |
| Maximum Current I _{mpp} (A) | 2.19 | 2.75 | 3.25 | 4.23 | 5.75 | 6.95 | 8.23 |
| Open Circuit Voltage V _{oc} (V) | 22.50 | 22.25 | 22.58 | 22.12 | 22.29 | 22.0 | 22.59 |
| Short Circuit Current I _{sc} (A) | 2.38 | 3.03 | 3.45 | 4.52 | 6.01 | 7.22 | 8.73 |
| Module Efficiency (%) | 12.53 | 12.71 | 13.57 | 14.62 | 14.69 | 14.70 | 15.13 |

1) STC:1000 W/m² irradiance, 25°C cell temperature, AM1.5g spectrum according to EN 60904-3.

Average relative efficiency reduction of 5% at 200 W/m² according to EN 60904-1.

Mechanical Data

| Length | 487 | 595 | 665 | 775 | 1025 | 1279 | 1495 |
|----------------------|---|-----|-----|-----|------|------|------|
| Width | 665 | 665 | 665 | 665 | 665 | 665 | 665 |
| Height | 35 | 35 | 35 | 35 | 35 | 35 | 35 |
| Weight | 4.5 | 5.2 | 6 | 7.6 | 8.9 | 11.2 | 12.5 |
| Junction Box | 1P65, 2 By Pass Diodes | | | | | | |
| Application Class | Class A [Safety Class II] | | | | | | |
| Superstrate | 3.2mm High Transmission Low Iron Tempered Glass | | | | | | |
| Cells | 36 Cells, 4BB/5BB Cells ,Poly Mono | | | | | | |
| Cell Encapsulant | EVA | | | | | | |
| Back Sheet | PET | | | | | | |
| Frame | Anodized Al Alloy Type 6063 | | | | | | |
| Mechanical Load Test | 5400 PA | | | | | | |

Temperature Coefficients (Tc)² permissible operating conditions


| Tc of Open Circuit Voltage (β) | -0.31%/C |
|--|-----------------|
| Tc of Short Circuit Current (α) | 0.0402%/C |
| Tc of Power (Y) | -0.426%/C |
| Maximum System Voltage | 1000V |
| NOCT | 45C <u>+</u> 2C |
| Temperature Range | -40C TO +85C |

²⁾ NOCT irradiance 800 W/m², ambient temperature 20°C, wind speed 1 m/sec


Warranty and Certifications

| Product Warranty** | 10 years |
|-------------------------------|--|
| Performance Warranty** | Linear power warranty for 25 years with 2.5% for 1st year degradation and 0.67% from year 2 to year 25 |
| Approvals and Certificates | IEC 61215, IEC 61730 Part 1 & 2 IEC 61701, IEC 62804 |

Typical I-V Curves



Performance Warranty



CAUTION: READ SAFETY AND INSTALLATION MANUAL BEFORE USING THE PRODUCT.

Specifications included in this datasheet are subject to change without notice. Electrical data without guarantee. Please confirm your exact requirement with the company representative while placing your order.

^{**} Refer to IB Solar Warranty Document For Terms & Conditions