



SolarEdge Single Phase Inverters

SE2200H, SE3000H, SE3500H, SE3680H
SE4000H, SE5000H, SE6000H



INVERTERS

Optimized installation with HD-Wave technology

- Specifically designed to work with power optimizers
- Record-breaking efficiency
- Extremely small, lightweight and easy to install
- High reliability without any electrolytic capacitors
- Built-in module-level monitoring
- Outdoor and indoor installation
- Compatible with the StorEdge Interface for Smart Energy Management StorEdge™ applications





Single Phase Inverters

SE2200H, SE3000H, SE3500H, SE3680H
SE4000H, SE5000H, SE6000H

	SE2200H	SE3000H	SE3500H	SE3680H	SE4000H	SE5000H	SE6000H		
OUTPUT									
Rated AC Power Output	2200	3000	3500	3680	4000	5000 ⁽¹⁾	6000	VA	
Maximum AC Power Output	2200	3000	3500	3680	4000	5000 ⁽¹⁾	6000	VA	
AC Output Voltage (nominal)	220 / 230								Vac
AC Output Voltage Range	184 - 264.5								Vac
AC Frequency (nominal)	50 / 60 ± 5								Hz
Maximum Continuous Output Current	10	14	16	16	18.5	23	27.5	A	
Residual Current Detector / Residual Current Step Detector	300 / 30								mA
Utility Monitoring, Islanding Protection, Country Configurable Thresholds	Yes								
INPUT									
Maximum DC Power	3400	4650	5425	5700	6200	7750	9300	W	
Transformer-less, Ungrounded	Yes								
Maximum Input Voltage	480								Vdc
Nominal DC Input Voltage	380								Vdc
Maximum Input Current	6.5	9	10	10.5	11.5	13.5	16.5	Adc	
Reverse-Polarity Protection	Yes								
Ground-Fault Isolation Detection	600kΩ Sensitivity								
Maximum Inverter Efficiency	99.2								%
European Weighted Efficiency	98.3	98.8		99				%	
Nighttime Power Consumption	< 2.5								W
ADDITIONAL FEATURES									
Supported Communication Interfaces	RS485, Ethernet, ZigBee (optional), WiFi (optional), Cellular (optional)								
Smart Energy Management	Export Limitation, StorEdge applications								
STANDARD COMPLIANCE									
Safety	IEC-62109-1/2, AS-3100								
Grid Connection Standards	AS-4777, VDE-AR-N-4105, VDE 0126-1-1, UTE C15-712, G83/2, G59/3, CEI-021, EN 50438, IEC61727, IEC62116, ÖNORM, TF3.2.1, C10-11, NRS 097-2-1								
Emissions	IEC61000-6-2, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12, FCC Part 15 Class B								
INSTALLATION SPECIFICATIONS									
AC Output - Supported Cable Diameter	9 - 16								mm
AC - Supported Wire Cross Section	1 - 16								mm ²
DC Input	1 x MC4				2 x MC4 pair				
Dimensions (H x W x D)	280 x 370 x 142								mm
Noise	< 25								dBA
Weight	9.5								kg
Cooling	Natural Convection								
Operating Temperature Range	-20 to +60 ⁽²⁾ (-40°C option)								°C
Protection Rating	IP65 - Outdoor and Indoor								

⁽¹⁾ 4600VA in Germany
⁽²⁾ De-rating from 50°C



RoHS

Sold in India by:
Nitashi Solar
Call: +91-9834653792
Email: info@nitashi.in
Web: www.nitashi.in